



## EtnaFoam FA 2056

**OVERVIEW:** EtnaFoam FA 2056 is an effective 100% active defoamer and antifoam based on fatty alcohols, fatty acids, surfactants, paraffinic oil, and hydrophobized silica. The material can be used in a variety of applications where silicone is not acceptable. Etna Foam FA 2056 can be added directly to most liquid mediums to defoam with a persistent effect that prevents foam from recurring. EtnaFoam FA 2056 does not contain any reportable hazardous ingredients.

**CHEMICAL NAME:** Fatty Alcohol, Fatty Acid, Paraffinic Oil

**FUNCTIONS:** Defoamer

### SPECIFICATIONS:

<b>Appearance:</b>	Opaque Yellow to Straw Colored
<b>Viscosity:</b>	Liquid 400 to 850 cps
<b>Defoaming:</b>	Equal to Standard
<b>Solubility 1% at 25C:</b>	Translucent

### MARKET APPLICATIONS:

- Textiles – Defoamer in textile processing and production
- Water Treatment – Wastewater treatment in manufacturing
- Paints and Coatings – Defoamer in paints and coatings
- Chemical Manufacturing – Defoamer formulations

### SEE SDS FOR STORAGE, HANDLING AND IN CASE OF SPILLS

DISCLAIMER: The information contained herein is believed to be accurate as of the date provided, but Ascent Chemicals (and its subsidiaries or affiliates) makes no guarantees or warranties of any kind, express or implied, as to the accuracy of the information or the use of the product. Because of the variations in methods, conditions, and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for any particular application. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself.