



EtnaFoam SE 5

OVERVIEW:

EtnaFoam SE 5 is a cost-effective silicone emulsion antifoam with 5% active silicone, providing reliable foam suppression at a lower concentration for reduced dosing. Part of a series available in various strengths (3, 5, 10, 20, and 30), it combines silicone and hydrophobized silica for rapid foam knockdown and moderate long-term control. An economical solution, EtnaFoam SE 5 is ideal for processes requiring effective foam management with limited silicone content.

CHEMICAL NAME: Silicone

FUNCTIONS: Defoamer

SPECIFICATIONS:

Appearance:	Opaque Off-White Viscous
Viscosity @ 25C:	Liquid 1000-2000 cps
pH Neat	6.5 to 8.5
1% Emulsification	Translucent
% Silicone Base	4-6%
Defoaming Test	Must Defoam Aggressively

MARKET APPLICATIONS:

- Textiles - Defoamer for fabric dyeing.
- Oil and Gas - Defoamer for drilling muds.
- Mining - Defoamer for flotation tanks.
- Water Treatment - Defoamer for municipal water.

SEE SDS FOR STORAGE, HANDLING AND IN CASE OF SPILLS

DISCLAIMER: The information contained herein is believed to be accurate as of the date provided, but Ascent Chemicals (and its subsidiaries or affiliates) makes no guarantees or warranties of any kind, express or implied, as to the accuracy of the information or the use of the product. Because of the variations in methods, conditions, and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for any particular application. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself.