



SierraMul HT

OVERVIEW: SierraMul HT is a fatty amidoamine and solvent based high temperature emulsifier. It is designed to be used as a formulation additive in drilling fluids to boost efficiency, emulsion and stability and control viscosity.

CHEMICAL NAME: Fatty Amidoamine

FUNCTIONS: Emulsifier

SPECIFICATIONS:

Appearance:	Clear Amber
Acid Value:	Liquid 68-130
Amine Value:	0-20
%Solids:	85-100
Viscosity:	0-2000 cps

MARKET APPLICATIONS:

- Oil & Gas – Drilling muds, oil production
- Metal Working – Metal Working Fluids
- Chemical Manufacturing – Raw material for Imidazoline quats

SEE SDS FOR STORAGE, HANDLING AND IN CASE OF SPILLS

DISCLAIMER: The information contained herein is believed to be accurate as of the date provided, but Ascent Chemicals (and its subsidiaries or affiliates) makes no guarantees or warranties of any kind, express or implied, as to the accuracy of the information or the use of the product. Because of the variations in methods, conditions, and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the products for any particular application. The user expressly assumes all risk and liability, whether based in contract, tort or otherwise, in connection with the use of the information contained herein or the product itself.

www.ascentchem.com